



## ioSafe Duo

Two copies of your data, both safe from disaster



### FIREPROOF

The ioSafe Duo is built to survive office and home fires – so you can get back up and running fast.



### WATERPROOF

Your work should survive broken pipes, floods, or the fire department's hose. Enter the ioSafe Duo, which protects data for up to 3 days in up to 10 feet of water.



### TWICE THE BACKUP

The ioSafe Duo is configured to create two backups of your data simultaneously, meaning that should one of the two drives fail, your data will remain safe and can be rebuilt on a new drive.



### DATA RECOVERY SERVICE

Should disaster strike, whether in the form of fire, water, or simply a failed hard drive, we'll help you get back in business. We'll even provide forensic data recovery if necessary!



### PERFORMANCE

The Duo is fast. Seriously fast. The 10 Gbps Duo connects to your computer with either a USB Type-C or standard Type-A cable.



### THEFTPROOF

With a built-in Kensington security slot and our optional floor mount and padlock kit, the Duo can be physically secured anywhere.

# ioSafe Duo

## Product Specifications

### Data Protection

DataCast™ Fire Protection  
HydroSafe™ Water Protection  
RAID Protection  
Security Protection

Protects data from fire. Up to 1550°F, 30 minutes per ASTM E-119.  
Protects data from flood. Fully submersed, fresh or salt water, 10 foot depth, 72 hours.  
RAID 1 by default. Can be configured to RAID 0, JBOD, or SPAN.  
Kensington Security Slot. Optional Floor Mount / Padlock Kit.

### Media and Connectivity

Internal HDD/SSD  
Hot Swappable HDD  
External Ports  
Supported Clients

3.5" SATA x2  
No  
USB 3.0 x3 (Type-C x2, Type-A)  
Windows 10, 8.1 and 7, macOS 10.13 "High Sierra" or newer, most Linux distributions

### Physical

Size (HxWxD)  
Weight  
Power Supply Unit  
Operating Temperature  
Storage Temperature  
Relative Humidity  
Supported RAID Type

5.9in x 11.5in x 9.06in (150mm x 292mm x 230mm)  
23.8 pounds (10.80 kg) (unpopulated)  
60W 12V 5A Adapter  
5°C to 35°C (40°F to 95°F)  
-10°C to 70°C (15°F to 155°F)  
5% to 95%RH  
RAID 1 (default), RAID 0, JBOD, SPAN

### Environment and Packaging

Environment  
Package Content  
Optional Accessories  
Warranty  
Data Recovery Service

RoHS Compliant  
Main Unit, AC Power Cord, USB Type-C to Type-C cable, USB Type-A to Type-C cable, Quick Start Guide  
Floor Mount / Padlock Kit  
Diskless: 2 years / With factory loaded hard drives: 2 years and 2 years Data Recovery Service  
Upgradeable to 5 year warranty and 5 year Data Recovery Service. Certain limitations apply. See website for details.

