



ioSafe SoloPro + Data Recovery Service

The world's only business-class fireproof, waterproof hard drive



FIREPROOF

Protects against data loss in fire up to 1550°F,
1/2 hour Per ASTM E119



WATERPROOF

Protects data from flood, full submersion, 10' depth,
72 hours, fresh or salt water



BUSINESS-CLASS COMPATIBILITY

Provides full support for Windows Server and Linux



DATA RECOVERY SERVICE

Forensic data recovery available with advanced
replacement included



ACTIVE AIRFLOW COOLING

Ensures optimum operating temperature



THEFTPROOF

Built in Kensington security slot or bolt down with
anti-theft tab



USB 3.0

Data transfer up to 5Gb/s

ioSafe SoloPro External Hard Drive

Product Specifications

Operational Details

- Single 3.5 SATA disk
- Quiet forced air cooling
- Multi-platform compatibility with Mac & PC/Windows
- Microsoft Windows Server and Linux compatible
- USB 3.0 Interface

Disaster & Security Specifications

- Fire protection - 1550°F, 1/2 hour per ASTM E119
- Flood / Submersion protection - to 10 feet water depth, 72 hours
- Proven data protection and recovery
- Tested per UL, FCC and CE Standards
- Physical theft protection
- Cable lock or floor mount
- Kensington® Lock Compatible

Support

- Data Recovery Service available
- Advanced Replacement included for warranty/DRS exchanges
- Expedited shipping for DRS support

Inside The Box

- ioSafe SoloPRO External Hard Drive
- USB Cable
- Power Supply
- Owners Manual and Warranty

Electrical

- Electrical - AC input
- Voltage: 80 ~ 264 VAC at 50/60 HZ
- Typical Power Consumption: < 25W

System Requirements

- Intel Pentium II 350 Mhz-compatible or Mac G3 processor & greater
- USB support for Microsoft Windows 7/Vista/XP, Windows Server, Mac OS 8.6 & greater, Linux Server or Linux based NAS devices
- For USB 3.0 speeds, the system must support applicable specifications
- For capacities of 3TB and higher, support may be limited to Windows 7, Server 2008, Linux and Mac

Operating Environment

- Operating: 0-35° C (95°F)
- Non-operating: 0-1550°F, 1/2 hr per ASTM E119
- Operating Humidity: 20% - 80% (non-condensing)
- Non-operating Humidity: 100%, Full water immersion, 10 feet, 3 days.

Physical

- Size: 5.0"W x 7.1"H x 11.0"L
- Weight: 15 lbs